

Touch-it XELO VESA glass 21,5

Datasheet



- **Made in Germany**
- **Multitouch**
- **Aluminium Silver Housing**
- **Ultra Compact Design, Fanless**
- **VESA 75 / 100**

PANEL

LCD Size	21.5 inch (54.6 cm)
Resolution	1920 x 1080
Aspect Ratio	16 : 9
Technology	TFT
Colours	16.7M
Backlight	LED
Backlight Life Time	30,000 h
Luminance*	250 cd/m²
Contrast Ratio*	3000 : 1
Viewing Angle* (right/left/up/down)	89°/89°/89°/89°
Touch	Projected Capacitive Touch, Anti-Glare, Multitouch (not supported in WS7E)

*The values are referring to the displays only.

SYSTEM

CPU	AMD® GX-415GA Quad Core™ 1.5 GHz 64 Bit, 2 MB Cache	Intel® Core™ i5-4300U Dual Core 1.9 GHz 64 Bit, 3 MB Cache
Chipset	Integrated in APU	Integrated in Intel® 4th Generation Core™ i U-series
Graphic	Radeon HD 8330E 500 MHz	Intel® HD Graphics 4400 200 MHz
Memory	4 GB DDR3L / 8 GB DDR3L	
Storage	32 / 64 / 128 GB MLC SSD / 1 TB HDD	
BIOS	AMI BIOS, Supports ACPI Function	
Wake on LAN	Yes	
H/W Status Monitoring	Supports Power Supply Voltages and Temperature Monitoring	
CMOS Battery	Lithium Battery	
Operating System	Windows® Embedded Standard 7 (WS7P) Windows® Embedded Standard 7 (WS7E) Windows® Embedded 8 Standard Windows® 10 IoT Linux	

Touch-it XELO VESA glass 21,5

Datasheet

STANDARD INTERFACES


USB	2 x USB Host 3.0 (Type A)
Ethernet	2 x 1 Gbit Ethernet
Communication	1 x RS-232 / RS-485 (BIOS setting)
Video	1 x DVI-I

OPTIONAL INTERFACES

USB	4 x USB Host 2.0 (Type A, max. Total Current 0.5 A)
WLAN	1 x 802.11 ac/a/b/g/n (2.4 GHz, 5 GHz)


POWER SUPPLY

Supply Voltage	24 VDC $\pm$ 20%
Power Consumption (nominal/max)	AMD® Quad Core: 17 W / 32 W Intel® Core™ i5: 20 W / 41 W
Power Button	Optional
Power Connector	Phoenix 3-pol MC 1,5/ 3-STF-3,5 BK (screwable) / Phoenix 3-pol MC 1,5/ 3-ST-3,5 BK



INTERFACES

PIN	Signal Name COM	
	RS-232	RS-485
1	DCD	DATA-
2	RX	DATA+
3	TX	NC
4	DTR	NC
5	Ground	Ground
6	DSR	NC
7	RTS	NC
8	CTS	NC
9	RI	NC



Touch-it XELO VESA glass 21,5

Datasheet

MECHANICAL & ENVIRONMENTAL


Housing Front	Glass, Black Frame
Housing	Aluminium / Silver
Dimensions	535.7 mm x 327.2 mm x 57 mm
Mounting	VESA MIS-D, 75, C VESA MIS-D, 100, C
Weight	5.8 kg
Cooling	Passive
Operating Temperature	0 ~ 50 °C
Storage Temperature	-10 ~ 70 °C
Humidity	5 ~ 80% (non condensing)
Protection Class	IP65 (IP20 rear)
Certification	CE, EN55022, EN55024, DIN EN ISO 9001

Never cover the Touch-it XELO VESA glass 21,5 completely or build it in a small closed and unvented housing.


Touch-it XELO VESA glass 21,5

Datasheet


DIMENSIONS




FRONT VIEW



BOTTOM VIEW



REAR VIEW



SIDE VIEW

Touch-it XELO VESA glass 21,5

Datasheet

ORDERING INFORMATION

Art. No.:	CPU		RAM		Storage				Optional Interfaces		
	AMD Quad-Core	Intel i5	4 GB	8 GB	32 GB SSD	64 GB SSD	128 GB SSD	1 TB HDD	4 x USB	WLAN	Power Button
E742116	☒	☐	☒	☐	☒	☐	☐	☐	☐	☐	☒
E742121	☐	☒	☒	☐	☐	☐	☒	☐	☒	☐	☒
E742125	☐	☒	☒	☐	☐	☒	☐	☒	☒	☒	☒
E742128	☒	☐	☒	☐	☐	☒	☐	☐	☐	☐	☒
E742131	☒	☐	☒	☐	☒	☐	☐	☐	☒	☐	☐

DISCLAIMER

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.



CHRIST ELECTRONIC SYSTEMS GMBH
MANUFACTURE OF INDUSTRIAL ELECTRONICS

CONTACT

Christ Electronic Systems GmbH
 Alpenstraße 34
 87700 Memmingen
 Phone: +49 8331/ 83710
www.christ-es.de

FROM IDEAS TO REALITY

We are a German developer and manufacture of innovative HMI-systems for demanding industrial applications. Christ offers an extensive range of

TOUCH PANEL PCs	x86 & ARM
TOUCH MONITORS	7" – 24"
SINGLE BOARD COMPUTER	Windows & Linux
VISUALISATION SYSTEMS	HMI & SCADA

Copyright / © Christ Electronic Systems GmbH
a member of the Christ Company Group

5 / 5

Feb. 2017, Revision 05
Document No.:E462376