

# Touch Industrial PC VESA 18.5

## Datasheet

- Panel
- System
- Interfaces
- Power Supply
- Mechanical & Environmental
- Ordering Information



### Panel

LCD Size	18.5 inch (47.0 cm)
Resolution	1366 x 768
Aspect Ratio	16 : 9
Technology	TFT
Colours	16.7 M
Backlight	LED
Backlight Life Time	50,000 h
Luminance*	450 cd/m <sup>2</sup>
Contrast Ratio*	1000 : 1
Viewing Angle* (right/left/up/down)	85°/85°/80°/80°
Touch	Projected Capacitive Touch, Multitouch, Anti-Glare

\*The values are referring to the display only.

### System

CPU	Intel® Celeron® N3350 1.1 GHz
Graphic	Intel® HD Graphics 500 200 MHz
Memory	4 GB DDR3L
Storage	64 GB 3D TLC SSD
BIOS	AMI Optio 5 BIOS
Wake on LAN	Yes
H/W Status Monitoring	Supports Power Supply Voltage and Temperature Monitoring
CMOS Battery	Lithium Battery (CR2450/610 mAh)
RTC	Internal RTC
TPM	TPM 2.0 (SLB9670)
Watchdog	Yes
RAID	No

# Touch Industrial PC VESA 18.5


## Datasheet

### Interfaces

<b>USB</b>	2 x USB Host 3.0 (Type A)
<b>Ethernet</b>	2 x 1 Gbit Ethernet (2 x Intel I211AT)
<b>Communication</b>	1 x RS-232 / RS-485 / RS-422 (RJ50) (BIOS setting)
<b>Video</b>	1 x DisplayPort 1.0 *

\* DisplayPort 1.0 does not allow compatibility with HDMI and DVI-I. Therefore an active adapter with properties of the DisplayPort 1.1 (DP++) is necessary.

### INTERFACES



#### COM Connector Pinning

PIN	RS-232	RS-422	RS-485
1	DSR	NC	NC
2	Ground	Ground	Ground
3	Ground	Ground	Ground
4	TXD	RX+	NC
5	RXD	TX+	DATA+
6	DCD	TX-	DATA-
7	DTR	RX-	NC
8	CTS	NC	NC
9	RTS	NC	NC
10	RI	NC	NC

### Power Supply

<b>Supply Voltage</b>	12 - 24 VDC $\pm$ 20 %
<b>Power Consumption (max*)</b>	up to 40 W
<b>Power Button</b>	No
<b>Power Connector</b>	Phoenix 3-pin MC 1,5/ 3-STF-3,5 BK (screwable)
<b>Fuse</b>	10 A, time lag, non-exchangeable

\*max. periphery consumption included (e.g. 1 x USB 2.0 equals 2.5 W)

# Touch Industrial PC VESA 18.5

## Datasheet

### Mechanical & Environmental

<b>Housing Front</b>	Glass, Black Frame
<b>Housing</b>	Aluminium / Silver
<b>Dimensions</b>	477 x 293 x 60 [mm]
<b>Mounting</b>	VESA MIS-D, 75 / VESA MIS-D, 100
<b>Weight</b>	max. 5.0 kg
<b>Cooling</b>	Passive
<b>Operating Temperature</b>	0 ~ 50 °C
<b>Storage Temperature</b>	-10 ~ 70 °C
<b>Humidity</b>	5 ~ 80 % (non condensing)
<b>Protection Class</b>	IP65 (IP20 rear)
<b>Certification</b>	CE, EN55032 Class A, EN55035

Never cover the Touch Industrial PC VESA 18.5 completely on the back or build it in a small closed and unvented housing.

Detailed size information can be found in the technical drawing under the following link:

[Technical drawing VESA 18.5](#)

# Touch Industrial PC VESA 18.5

## Datasheet

### Ordering Information

Ordering-No.	
PA10007311	Touch Industrial PC VESA 18.5

### Disclaimer

Christ Electronic Systems GmbH reserves the right to change the information, designs and technical data contained in this documentation without prior notice, as the products are subject to constant further development. No guarantee is given that the data is complete, up-to-date and correct. In this document, all brand names as well as software and hardware designations used are subject to the respective companies, general trademark, brand or patent protection.

### Contact

Christ Electronic Systems GmbH  
Alpenstraße 34  
87700 Memmingen

Phone:  
+49 8331 8371-0 (Main Office)  
+49 8331 8371-500 (Service)

Mail:  
[info@christ-es.de](mailto:info@christ-es.de)

Homepage:  
<https://www.christ-es.com>

© Christ Electronic Systems GmbH