

# Touch Industrial Distance Monitor Front Panel 10.1

#### Datasheet

- Panel
- Interfaces
- Power Supply
- Mechanical & Environmental
- Ordering Information



#### **Panel**

LCD Size	10.1 inch (25.7 cm)
Resolution	1280 x 800
Aspect Ratio	16:10
Technology	TFT
Colours	16.2M
Backlight	LED
Backlight Life Time	50,000 h
Luminance*	500 cd/m <sup>2</sup>
Contrast Ratio*	800 : 1
Viewing Angle* (right/left/up/down)	85°/85°/85°/85°
Touch	Projected Capacitive Touch, Multitouch, Anti-Glare

<sup>\*</sup>The values are referring to the display only.

#### Interfaces

USB	2 x USB Host 2.0 (Type A)
Ethernet	1 x 1 Gbit Ethernet (RJ45 with PoE
PWR X11 ETH (PoE) X21	USB 2.0 X31 USB 2.0 X32

## **Power Supply**

Supply Voltage	24 VDC ± 20 %
Power Consumption (max*)	up to 20 W
Power Button	No
Power Connector	Phoenix 3-pin MC 1,5/ 3-STF-3,5 BK (screwable)
Fuse	2.5 A, time lag, non-exchangeable, Type: Littelfuse 045202.5MLR

<sup>\*</sup>max. periphery consumption included (e.g. 1 x USB 2.0 equals 2.5 W)

Doc.No.: PA10012047 1 / 3 Nov. 2022, Revision 00



# **Touch Industrial Distance Monitor Front Panel 10.1**

#### Datasheet

### Mechanical & Environmental

Housing Front	Glass, Black Frame
Housing	Aluminium / Silver
Dimensions	273 x 190 x 57 [mm]
Cutout	262 x 179 [mm] rounded corners with radius 10 mm, see technical drawing
Weight	max. 2.3 kg
Cooling	Passive
Operating Temperature	0 ~ 50 °C
Storage Temperature	-10 ~ 70 °C
Humidity	5 ~ 80 % (non condensing)
Protection Class	IP65 (IP20 rear)
Certification	CE, EN55032 Class A, EN55035

Never cover the Touch Industrial Distance Monitor Front Panel 10.1 completely on the back or build it in a small closed and unvented housing.

Detailed size information can be found in the technical drawing under the following link:

Technical drawing Front Panel 10.1"

Doc.No.: PA10012047 2 / 3 Nov. 2022, Revision 00



## **Touch Industrial Distance Monitor Front Panel 10.1**

#### **Datasheet**

### **Ordering Information**

Ordering-No.	
PA10008514	Touch Industrial Distance Monitor Front Panel 10.1

#### Disclaimer

Christ Electronic Systems GmbH reserves the right to change the information, designs and technical data contained in this documentation without prior notice, as the products are subject to constant further development. No guarantee is given that the data is complete, up-to-date and correct. In this document, all brand names as well as software and hardware designations used are subject to the respective companies, general trademark, brand or patent protection.

#### Contact

Christ Electronic Systems GmbH Alpenstraße 34 87700 Memmingen

Phone:

+49 8331 8371-0 (Main Office) +49 8331 8371-500 (Service) Mail: info@christ-es.de

Homepage:

https:\\www.christ-es.com

© Christ Electronic Systems GmbH

Doc.No.: PA10012047 3 / 3 Nov. 2022, Revision 00