

Touch Industrial Distance Monitor VESA 10.4

Datasheet

- Panel
- Interfaces
- Power Supply
- Mechanical & Environmental
- Ordering Information



Panel

LCD Size	10.4 inch (26.4 cm)
Resolution	1024 x 768
Aspect Ratio	4:3
Technology	TFT
Colours	16.2 M
Backlight	LED
Backlight Life Time	30,000 h
Luminance*	350 cd/m ²
Contrast Ratio*	1200 : 1
Viewing Angle* (right/left/up/down)	88°/88°/88°/88°
Touch	Projected Capacitive Touch, Multitouch, Anti-Glare

*The values are referring to the display only.

Interfaces

USB		2 x USB Host 2.0 (Type A)	
Ethernet 1 x 1 Gbit Ethernet (RJ45 with		1 x 1 Gbit Ethernet (RJ45 with PoE)	
PWR X11	ETH (PoE) X21	USB 2.0 X31 USB 2.0 X32	

Power Supply

Supply Voltage	24 VDC ± 20 %
Power Consumption (max*)	up to 15 W
Power Button	No
Power Connector	Phoenix 3-pin MC 1,5/ 3-STF-3,5 BK (screwable)
Fuse	2.5 A, time lag, non-exchangeable, Type: Littelfuse 045202.5MLR

*max. periphery consumption included (e.g. 1 x USB 2.0 equals 2.5 W)



Touch Industrial Distance Monitor VESA 10.4

Datasheet

Mechanical & Environmental

Housing Front	Glass, Black Frame
Housing	Aluminium / Silver
Dimensions	274 x 215 x 58 [mm]
Mounting	VESA MIS-D, 75 / VESA MIS-D, 100
Weight	max. 2.3 kg
Cooling	Passive
Operating Temperature	0 ~ 50 °C
Storage Temperature	-10 ~ 70 °C
Humidity	$5 \sim 80$ % (non condensing)
Protection Class	IP65 (IP20 rear)
Certification	CE, EN55032 Class A, EN55035

Never cover the Touch Industrial Distance Monitor VESA 10.4 completely on the back or build it in a small closed and unvented housing.

Detailed size information can be found in the technical drawing under the following link: <u>Technical drawing VESA 10.4</u>



Touch Industrial Distance Monitor VESA 10.4

Datasheet

Ordering Information

Ordering-No.

PA10008577

Touch Industrial Distance Monitor VESA 10.4

Disclaimer

Christ Electronic Systems GmbH reserves the right to change the information, designs and technical data contained in this documentation without prior notice, as the products are subject to constant further development. No guarantee is given that the data is complete, up-to-date and correct. In this document, all brand names as well as software and hardware designations used are subject to the respective companies, general trademark, brand or patent protection.

Contact

Christ Electronic Systems GmbH Alpenstraße 34 87700 Memmingen

Phone:

+49 8331 8371-0 (Main Office) +49 8331 8371-500 (Service) Mail: info@christ-es.de

Homepage: https://www.christ-es.com

© Christ Electronic Systems GmbH