

## Datasheet

- Panel
- System
- Interfaces
- Power Supply
- Mechanical & Environmental
- Ordering Information



#### Panel

LCD Size	12.1 inch (30.7 cm)
Resolution	1280 x 800
Aspect Ratio	16 : 10
Technology	TFT
Colours	16.7 M
Backlight	LED
Backlight Life Time	50,000 h
Luminance*	400 cd/m <sup>2</sup>
Contrast Ratio*	1000 : 1
Viewing Angle* (right/left/up/down)	88°/88°/88°/88°
Touch	Projected Capacitive Touch, Multitouch, Anti-Glare

\*The values are referring to the display only.

#### System

CPU	NXP® i.MX 8M Plus QuadCore 1.8 GHz
Graphic	3D: Vivante™ GC7000UL / 2D: Vivante™ GC520L
Memory	1 GB DDR4
Storage	8 GB eMMC FLASH
CMOS Battery	Lithium Battery (CR2450/620 mAh)
RTC	RV-8803-C7 ultra precise ±3 ppm


## Interfaces

Power	1 x Phoenix 3-pin MC 1,5/ 3-STF-3,5 BK (screwable), PWR X11
USB	2 x USB Host 3.0 (Type A), X31, X32
Network	2 x 1 Gbit Ethernet (RJ45)
Serial	1 x RS-232 (Sub-D)
MicroSD	1 x MicroSD Slot



## Datasheet

#### **INTERFACES**



#### PWR X11

- PIN Signal
- 1 Ground
- 2 Functional Earth
- **3** 12 24 VDC ± 20 %

#### Serial X41

PIN	RS-232
1	
2	RX
3	ТХ
4	
5	Ground
6	
7	
8	
9	

### **Power Supply**

Supply Voltage	12 - 24 VDC ± 20 %
Power Consumption (max*)	up to 30 W
Power Button	No
Power Connector	Phoenix 3-pin MC 1,5/ 3-STF-3,5 BK (screwable), PWR X11
Fuse	5 A, very fast-acting, non-exchangeable, Type: Littelfuse 0451 005.

\*max. periphery consumption included (e.g. 1 x USB 2.0 equals 2.5 W)



### Datasheet

#### Mechanical & Environmental

Housing Front	Glass, Black Frame
Housing	Aluminium / Silver
Dimensions	325 x 222 x 58 [mm]
Mounting	VESA MIS-D, 75 / VESA MIS-D, 100
Weight	max. 2.7 kg
Cooling	Passive
Ambient Temperature	0 ~ 50 °C
Storage Temperature	-10 ~ 70 °C
Humidity	$5 \sim 80$ % (non condensing)
Protection Class	IP65 (IP20 rear)
Certification	CE, EN55032 Class A, EN55035

Never cover the Touch Industrial PC VESA 12.1 completely on the back or build it in a small closed and unvented housing.

Detailed size information can be found in the technical drawing under the following link: <u>Technical drawing VESA 12.1</u>



Datasheet

## **Ordering Information**

Ordering-No.

PA10009655

Touch Industrial PC VESA 12.1

Datasheet valid from device revision 0

#### Disclaimer

Christ Electronic Systems GmbH reserves the right to change the information, designs and technical data contained in this documentation without prior notice, as the products are subject to constant further development. No guarantee is given that the data is complete, up-to-date and correct. In this document, all brand names as well as software and hardware designations used are subject to the respective companies, general trademark, brand or patent protection.

#### Contact

Christ Electronic Systems GmbH Alpenstraße 34 87700 Memmingen

#### Phone:

+49 8331 8371-0 (Main Office) +49 8331 8371-500 (Service) Mail: info@christ-es.de

Homepage: https://www.christ-es.com

© Christ Electronic Systems GmbH